

**HYCO**  
*Manufacturing Ltd*  
**HD700**

# Hycos Wall Mounted hairdryer

**Hycos Manufacturing Ltd**  
California Drive  
Castleford  
WF10 5QH

Tel 01977 517555  
[www.hycos.co.uk](http://www.hycos.co.uk)

version 1.1 Nov 2007

## Instruction Manual

## Hyco Manufacturing Ltd

Hyco Wall Mounted Hair Dryer

### Technical specification

Model	HD700
Power	700W 230V 50Hz
IP Rating	IPX4
CE Approvals	EN-60335 CE LVD/EMC

### General

Thank you for purchasing a product from Hyco Manufacturing Ltd.

Please read these guidelines before installation. If in any doubt, seek the advice of a qualified electrician or call our technical support line on 01977 517555.

### Product Features

The HD700 Wall Mounted Hair Dryer is suitable for hotels, gyms and similar applications.

Because all the electrical and heating components are located within the fixed wall mounted body of the product this unit is generally safer than a portable hair drying appliance.

**⚠** It remains essential that the unit location is consistent with the product IP rating and that due regard is paid to the possibility of vandalism.

This model will start and stop automatically when the nozzle is removed from the base and will automatically switch off after approximately 15 minutes of continuous use. To reset the timer replace the nozzle.

### Installation

**⚠** This model is rated IPX4. Site unit accordingly.

Drill a 6mm hole at the required location of the top of the base unit. Drill a second 6mm hole 267mm vertically below the first hole.

Fix the supplied plastic bracket to the lower hole using the supplied screw and plug. The bracket should point upwards.

Open the access plate located at the top of the unit using a cross head screwdriver and identify the upper rectangular fixing hole at the very top of the unit.

Hook the bottom of the unit to the wall bracket and screw the top of the unit to the wall using the remaining screw.

### Electrical Connection

Connection must be in accordance with the latest Edition of the Wiring Regulations.

The unit is pre-wired with a UK plug, but note that for bathroom use a direct connection to a fused spur is required.

It is possible to connect a cable directly to the back of unit so that there is no wiring visible to the user.

There is a knockout disk located next to the terminal block that is designed to give cable access for this purpose. A blanking grommet is enclosed that will allow the flex entry hole to be sealed.

Ensure access cover is securely replaced before use.

### Operation

Remove the nozzle from the base unit to start operation. Return to stop.

Clean product by wiping with a damp cloth. Do not use abrasive compounds or solvents.

### Warranty

This product is guaranteed for a period of one year against faulty components or workmanship.

**In the event of a warranty failure, Hyco will at its sole discretion repair or replace the unit.**

Unless expressly agreed in writing, this guarantee does not provide for on-site labour costs. Consequential costs are excluded.

### Technical Support

If you experience difficulties call our technical support on 01977 517555 between 8:30 and 5pm Monday to Friday.

**Goods should not be returned without first contacting the manufacturer and obtaining a returns authorisation number.**

### Hyco Manufacturing Ltd

California Drive  
Castleford  
WF10 5QH

Tel 01977 517555  
[www.hyco.co.uk](http://www.hyco.co.uk)